

WEYB

Roll-on sealing tube



- Easy, “roll-on” way to insulate and seal cable connections up to 1kV.
- Made of EPDM rubber, resisting damage from exposure to moisture, ozone, fungus and temperature extremes from -60 to 150 .
- Dual-wall design with an entrapped lubricant, making installation fast and simple.
- Rolls on the cable with minimal effort, even at temperature below -25 .
- Ideal for use where heating is not allowed.
- Reusable.

Selection Table

Product No.	Tube length ±5/mm	Application range Cable outer diameter/mm
WEYB-14	160	12~20
WEYB-25	370	26~38

Technical Data

Property	Test Method	Standard Value
Ultimate Tensile	ISO 37	≥8.1MPa
Ultimate Elongation	ISO 34	≥750%
Ultimate Tensile after 136°Cx168h	ISO 37	9.5Mpa
Ultimate Elongation after 136°Cx168h	ISO 34	719.89
Water Absorption	ISO 62	0.3%
Dielectric Strength	IEC 60243	8kV/mm
Volume Resistivity	ASTM-D-2303	1.3x10 ¹⁵
Environmental Testing	RoHS	Meet the RoHS
Salt Spray Test	GB2423	No crack with ultimate elongation 770% certified by SGS.
Ozone Test	GB7762	No crack certified by SGS.
Low Temperature Ultimate Elongation	-60 °Cx4h	391.4%